

In the claims:

Please amend the claims as follows:

1-20. Canceled.

21. (New) An apparatus comprising:

a multi-axis interferometer comprising a polarizing beam splitter block having

(i) multiple output ports on a common face of the block, each output port positioned to transmit from within the block a corresponding intermediate beam derived from a common input beam, and

(ii) a polarizing beam splitting interface internal to the block and positioned to separate each intermediate beam into a measurement component and a reference component having different polarizations.

22. (New) The apparatus of claim 21, wherein at least some of the multiple output ports are partially reflective.

23. (New) The apparatus of claim 22, wherein the reflectivities of the output ports are selected to cause the output beams to have substantially equal intensities.

24. (New) The apparatus of claim 21, wherein the common input beam or a portion thereof is incident on each output port from within the block, and wherein each output port causes the propagation direction of the transmitted intermediate beam to differ from that of the incident beam.

25. (New) The apparatus of claim 24, wherein each output port diffracts the incident beam to transmit the intermediate beam.

26. (New) The apparatus of claim 24, wherein each output port refracts the incident beam to transmit the intermediate beam.

27. (New) The apparatus of claim 21, wherein the polarizing beam splitting interface causes the measurement and reference components to have orthogonal polarizations.

28. (New) The apparatus of claim 21, wherein the multi-axis interferometer further comprises a corner reflector positioned to redirect each intermediate beam towards the polarizing beam splitting interface.

29. (New) The apparatus of claim 22, wherein the block comprises a reflective coating on a face opposite the common face, the reflective coating positioned to redirect any beam portion internally reflected by one of the output ports to be incident on another of the output ports.

30. (New) The apparatus of claim 21, wherein the multi-axis interferometer further comprises a reference mirror positioned to reflect each of the reference components back towards the polarizing beam splitter interface, a reference wave plate positioned between the reference mirror and the polarizing beam splitter interface, and a measurement wave plate positioned between the polarizing beam splitter interface and a measurement object.

31. (New) The apparatus of claim 32, wherein the polarizing beam splitter interface is configured to recombine each measurement and reference component with one another after the measurement components make a pass to the measurement object, and wherein the multi-axis interferometer further comprises plurality of retro-reflectors each positioned to redirect a corresponding pair of the recombined components back to the polarizing beam splitter interface.

32. (New) A multi-axis interferometer comprising:  
a polarizing beam splitter block having

(i) multiple output ports on a common face of the block, each output port positioned to transmit from within the block a corresponding intermediate beam derived from a common input beam, and

Applicant : Andrew Eric Carlson  
Serial No. : 09/940,076  
Filed : August 27, 2001  
Page : 5 of 7

Attorney's Docket No.: 09712-119001 / Z-265

(ii) a polarizing beam splitting interface internal to the block and positioned to separate each intermediate beam into a measurement component and a reference component having different polarizations.